

WS-P20-P140

POLY-CRYSTALLINE MODULES

Type	Pmax(W)	Voc(V)	Isc(A)	Vm(V)	Im(A)	Size(mm)	Lay up	weight (KG)
WS-P20	20	21.7	1.27	17.5	1.15	560x350x25	2x18	2.6
WS-P25	25	21.7	1.59	17.5	1.43	650x350x25	2x18	3.2
WS-P30	30	21.6	1.94	17.4	1.73	425x670x30	4x9	3.5
WS-P35	35	22.0	2.1	17.9	1.96	425x670x30	4x9	3.5
WS-P40	40	22.1	2.39	18.0	2.22	463x670x30	4x9	4.1
WS-P45	45	21.8	2.84	17.6	2.56	540x670x30	4x9	4.6
WS-P50	50	22	3.16	17.4	2.87	630x670x30	4x9	5.4
WS-P55	55	22.0	3.3	18.0	3.06	630x670x35	4x9	5.4
WS-P60	60	22.0	3.59	18.0	3.33	686x670x35	4x9	5.9
WS-P65	65	21.7	4.12	17.5	3.71	775x670x35	4x9	6.5
WS-P70	70	22.0	4.20	17.9	3.91	775x670x35	4x9	6.5
WS-P75	75	21.7	4.77	17.5	4.29	866x670x35	4x9	6.8
WS-P80	80	22.1	4.82	18.0	4.44	866x670x35	4x9	6.8
WS-P85	85	22.1	5.09	18.0	4.73	920x670x35	4x9	7.3
WS-P90	90	21.8	5.55	17.6	5.11	1010x670x35	4x9	7.8
WS-P95	95	22.1	5.68	18.0	5.28	1010x670x35	4x9	7.8
WS-P100	100	21.7	6.21	17.5	5.71	1125x670x35	4x9	8.6
WS-P105	105	22.0	6.11	17.9	5.87	1125x670x35	4x9	8.6
WS-P110	110	21.7	6.94	17.6	6.25	1245x670x35	4x9	9.8
WS-P115	115	22.1	6.96	17.8	6.46	1245x670x35	4x9	9.8
WS-P120	120	22.2	7.08	18.3	6.59	1245x670x35	4x9	9.8
WS-P135	135	22.1	8.28	17.8	7.58	1480x670x35	4x9	11.7
WS-P140	140	22.2	8.31	18.1	7.73	1480x670x35	4x9	11.7